

## WELDPLAST S2 PVC



A screw specially designed for PVC was developed as the centrepiece of the new hand extruder.

With this and the other countless technical advances, the WELDPLAST S2 PVC is a device which is convincing in every situation.

- Multifunctional display
- Double sided, twist free wire intake
- Freely adjustable swivel-mounted handgrip
- Ergonomic construction
- Maintenance-free blower
- Low-noise, high power transmission
- Extruder screw ideal for PVC
- Easily adjustable air duct for all welding positions

### SPECIFICATIONS

135.724

Voltage	V~	230
Frequency	Hz	50/60
Material		PVC-U, HD-PE, LD-PE, PP (other materials on request)
Output Ø 3	kg/h	PVC-U: 0.9 –1.7   PE: 0.6 –1.3   PP: 0.5 –1.2
Output Ø	kg/h	PVC-U: 1.5 –2.7   PE: 1.0 –2.3   PP: 0.9 –2.0
Welding rod	mm	3/4
Size (L x W x H)	mm	450 × 98 × 260 (without welding shoe)
Weight	kg	5.8 (without mains connection cable)
Marking of conformity		
Certification scheme		CCA
Protection class I		

## ACCESSORIES



Tool rest for WELDPLAST S2

131.451 - Tool rest



Welding shoe complete, Fillet weld for WELDPLAST S2

118.887 - 5/6 mm  
118.885 - 8/10 mm  
119.139 - 15 mm  
119.140 - 20 mm



Welding shoe complete, V-seam for WELDPLAST S2

118.888 - V-seam 5/6 and X-seam 10/12  
118.889 - V-seam 8/10 and X-seam 15/20 mm  
119.202 - V-seam 12 and X-seam 25 mm  
119.203 - V-seam 15 and X-seam 30 mm  
119.204 - V-seam 20 and X-seam 35/40 mm